



REF: **VL-ONE**
Projector lift

Features :

- Easy to install a use.
- Three pantographs for more linearity.
- Two lines of drag, greater stability.
- Cable guidance system improved.
- Low noise and weight.
- Only fully folded 88 mm.
- Optimized for projectors up to 10kg.
- New anchorage system of the projector.

Technical data VL-ONE:

Motor:

Type:	Tubular Pluscreen
Model:	DM 35S-10
Motor par:	10 Nm
Speed RPM:	17
Thermal protection:	140° C
N° turn end of run:	40
Kind of protection:	IP 44
Cable wires:	4

Lift:

Max. travel:	80 cm
Travel time:	20 sg
Continuous working time:	240 sg
Supported weight:	10 Kg
Noise level:	<40 dB
End of run adjust:	Upper and Lower

Included accesories:

Ceiling bracket (3 ud)
M4 threaded spacer (3 ud)
Gap separating until M4 (3 ud)
Roof angle (4 ud)
Threaded rod M5x250 (4ud)
DIN 7985 M4x20 (4 ud)
DIN 985 M4 (6ud)
DIN 934 M5 (16 ud)
DIN 125 M4 (6 ud)
DIN 125 M5 (16 ud)

Optional accesories:

Radiofrequency remote control mod. MRF 1RP
Infrared remote control mod. MIR 1ER
VL ONE-Kit Marco, ceiling closure kit

Remark: All specifications are subject to change without notice.

Power Supply:

Power:	230 V AC 50 Hz
Consumption:	121W máx.

Working conditions:

Temperature:	-10°C~+50°C
Humidity:	5% a 50% RH (no condensation)

Housing:

Material:	Iron + Anodize Aluminium
Color:	Grey

Dimensions:

Wide:	452 mm
High:	88 mm
Depth:	433,4 mm

Weight:

8,5 Kg

Electrical diagram:

